

# KERRO SCALE P-5 (500G/0.001G EMF)

## Standard Function:

- Auto Shutt Off.
- Auto Outside Calibration.
- Auto Zero Tracking
- Auto Back Light.
- Low Battery Indication.
- Large Weighing Pan.
- Net weight Stable indication
- Large LCD Display/Optional double side display.
- Full Tare function.

## Technical Specification:



Model No.	BL 35002	BL-50002	BL-5003 EMF
<b>Range</b>	3500g	5kg	500g
<b>Div./Readabilty (Gm)</b>	0.01gm/10mg	0.01gm/10mg	0.001g/1mg
<b>Linearity</b>	<=0.03g	<=0.08g	<=0.002g
<b>Stability</b>	2s		5s
<b>Pan/Platform Size(mm/inch)</b>	160 mm Stainless Iron		130mm Stainless Iron
<b>Dimension</b>	295mm x 260mm x 110mm		
<b>Tare Range</b>	Full to Capacity		
<b>Calibration</b>	Auto Outside Calibration		
<b>Interface</b>	RS232C		
<b>Units of Measure</b>	g, kg, oz, ct, lb, GN		
<b>Display</b>	Large LCD(white Back Light) (LxW) 4.3"x1.2" (110x30 mm)		
<b>Operating Temperature</b>	5 °C~35 °C		
<b>Power Supply</b>	AC 110-240 V/50-60HZ		
	3V/100mA AC Adaptor (Optional)		
<b>Stability</b>	2s		
<b>More Function</b>	Counting, Percentage, Full Range Tare, Over-Load Protection Zero Tracking, Automatic Turn-Off, Under Weighing, Low Power Indicator		
<b>Net/Gross Weight (Approx.)</b>	2.8kg per pcs		4kg
<b>Sales Packaging</b>	1Pc/ Box		
<b>Material</b>	ABS		
<b>Certificate</b>	CE, C-Tick, ISO9001:2000, RoHs		
<b>Attachment</b>	User Manual, AC Adapter, Underhook		

**Application:**

Best used in Precise Weight measurement, in Research Fields, Schools, Laboratories.  
Best Quality.